

This information sheet is not a Safety Data Sheet, since our wires are only articles according REACH. They are neither Substances nor Components, and require no SDS. This information sheet is intended to give guidance to the user on any potential health, safety and environmental question associated with the use of this material. The information has been standardized within all European Manufacturers, members of EWWG : Europacable Winding Wire Group

**We declare that the Material conforms to the Environmental Specifications,  
as listed in the Ecodeclaration below**

<b>ENVIRONMENTAL MANAGEMENT SYSTEMS</b>	<b>UNI EN ISO14001: 2015</b> Certificate No: AMB351 dated 2018-09-18. Expiry Date: 2021-09-13
<b>MATERIAL</b>	<b>MAGNETEMP CA-200, MAGNETEMP A-220</b>
<b>MATERIAL DESIGNATION</b>	<b>Polyester (imide) enameled wire with (or without) polyamide-imide top coat or Polyamide-imide enameled wire</b>
<b>IEC STANDARDS</b>	IEC 60317-0, -28, -29, -58
<b>PURPOSE</b>	For use only as winding wires for electrical applications
<b>CHEMICAL COMPOSITION</b>	The film is a modified Polyester (imide) with polyamide-imide top coat on a copper conductor. Substrate: electrolytic copper 99.95 % purity. The material does not contain lead, mercury, cadmium, hexavalent chromium, polybromated biphenyl (PBB), polybrominated diphenylether (PBDE), Hexabromocyclododecan (HBCCD), Di(2-ethylhexyl)phthalat (DEHP), Butylbenzylphthalat (BBP), Dibutylphthalat (DBP) and Diisobutylphthalat (DIBP) according to European Union Directive 2011/65/EU (RoHS II) and pentaBDE, octaBDE according to European Union Directive 2003/11/EC.
<b>WEIGHTS AND DIMENSIONS</b>	Double coat wire: wire with base coat insulation plus overcoat insulation. Substrate: from 95 to 99.3 % in weight (average 97.5 %) Base coat insulation: from 0.6 to 4 % in weight (average 2.0 %) Overcoat insulation: from 0.1 to 1 % in weight (average 0.5 %)
<b>PHYSICAL PROPERTIES</b>	Solid material - stable up to its recommended maximum operating temperature of 200°C, for a minimum life of 20.000 hours. (220°C for MAGNETEMP A-220) Resistivity at 20 °C: Copper 0.0172413 Ωmm <sup>2</sup> /m
<b>HEALTH HAZARDS</b>	There are no known health hazards associated with this material when used for its specified purpose. If the enamel film is burnt, degradation products may be evolved which may require local exhaust ventilation.
<b>FIRE PRECAUTIONS</b>	In normal conditions of storage this material will not initiate nor support combustion. If this material is involved in a fire, the plastic spools, pallets and other packaging are combustible and may give off toxic fumes.
<b>HANDLING USE / PRECAUTIONS</b>	As this material is used in other manufacturing processes it is important that any safety devices on the winding machines are used in accordance with the manufacturers' instructions. Particular attention should be paid to subsequent operations such as soldering and bonding, local exhaust ventilation should be used if required. Care should be taken to prevent cuts from any sharp edges on the wire. When de-reeling, care should be taken to ensure that any loose ends from the end of the reel or from a wire break do not fly out and cause laceration injury. Care should also be taken to ensure that trapped wires do not cause the reel to be pulled up out of position. On site risk assessments should be carried out to determine the safe way of handling reels or packages containing wire.

<b>OCCUPATIONAL EXPOSURE STANDARDS</b>	No relevant standards for this type of coatings.
<b>TRANSPORTATION / STORAGE CONDITION</b>	<p>Enameled Winding Wire is not subject to any specific provisions within the European Community.</p> <p>Care should however be taken to ensure that all loads are secured and unable to move during transportation.</p> <p>The storage temperature should not exceed 60 °C. High humidity, condensation water or aggressive agents should be avoided. Recommended conditions are 25 °C at 60 % humidity and no direct solar radiation.</p> <p>Under optimum storage condition the maximum recommended shelf life is 6 months. These are standard values, after exceeding the time limit the properties of the wire have to be tested before use.</p>
<b>DISPOSAL PRECAUTIONS</b>	<p>a) Winding wires are used with other materials to form a component which is part of many different electrical equipment/apparatus. As far as the Directive on Electrical and Electronic Waste (WEEE 2002/96/CE) is concerned, it is the End of Life of the Electrical and Electronic Equipment/Apparatus that is important. The winding wire producers do not have a direct influence on the life of the equipment / apparatus.</p> <p>b) Winding wires are not equipment according the Directive WEEE 2002/96. The winding wire producers shall not be charged with the responsibility and the cost of recycling.</p> <p>c) Only for information the winding wires producers suggest to the owner of the enameled wires this environmental-friendly way of recycling the enameled copper wires coming from production waste, customer production waste or end of life of electric-electronic apparatus:  1) To separate the metal wire from the packaging or support.  2) To send the metal waste to the metal refinery in order to recover copper.  3) To send the packaging materials to the packaging producers for recycling.</p> <p>d) Wastes of enameled wires are considered by the current Regulations “recyclable materials” (not dangerous waste).  The Eurocode concerning enameled wires are:  16.01.18 non-ferrous metal  17.04.01 Copper, bronze and brass  17.04.02 Aluminum</p> <p>The Eurocode concerning the packaging are:  15.01.01 Paper and cardboard packaging  15.01.02 Plastic packaging  15.01.03 Wooden packaging  15.01.04 Metallic packaging  15.01.05 Composite packaging  15.01.06 mixed packaging</p>
<b>COMPANY ADDRESS</b>	<p><b>Essex Italy S.p.A</b> Via Circonvallazione, 2 15028 Quattordio Italy</p>